



Characteristics	Mirage Classic		
Description	• Solid prefinished hardwood flooring with tongues and grooves • Micro-V bevel (on 4 sides)		
Thickness	3/4" (19 mm)		
Width	2-1/4" (57 mm)	3-1/4" (83 mm)	4-1/4" (108 mm)
Length¹	Random lengths from 10" (250 mm) to 76" (1,930 mm)		
Installation	Nailed or stapled down (above and on grade)		
Subfloor	Wood		
Species	4 species: Red Oak, Oak, White Oak, Maple		
Grade	• Exclusive: Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a limited range of color variation. • Character: These floors are appreciated for their pronounced color variations. They feature open and closed knots, mineral streaks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.		
Color choice (Refer to 2025 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the Product Chart .		
Finish	Finishing system made of aluminum oxide and nanosilica particle composites suspended in UV cured polyurethane.		
	• DuraMatt® (5% gloss) • DuraMatt® X (10% gloss) • DurAlive™ (12% gloss) • Cashmere* uses Nanolinx® technology (18% gloss) • Nanolinx® Commercial (18% gloss)		
	UV Protection: All products		
	Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5		
Applicable standards	Surface Burning (ASTM-E-84): • FSI (Flame Spread Index) 100 to 150 Class C (depends on wood species) • SD (Smoke Development) 75 to 400 (depends on wood species)		Surface Burning (ULC-S-102-2): • FSV (Flame Spread Value) 100 to 150 (depends on wood species) • SD (Smoke Development) 200 to 300 (depends on wood species)
	Critical radiant flux (ASTM-E-648-94a): 0.25 to 0.40 watt/cm² (depends on wood species)		R value: R 0.6 to 0.8 (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (Classic) conform		
Provenance	Made in St-Georges, Qc, Canada.		
Use	Residential, light commercial or commercial		
Accessory	Round Stair Nosing, Square Stair Nosing, Matchable Square Stair Nosing, Round Reducer, Threshold, "T" Molding, Quarter Round, Wood Flush Mount Vent, Treads & Risers		
Warranty	• Structural lifetime limited warranty (Relative humidity must always be maintained within a range of 35% and 55%). • 35-year finish warranty for residential applications • 3-year finish warranty for light commercial applications • 5-year finish warranty for commercial applications with Nanolinx® Commercial		
Packaging	2-1/4" (57 mm)	3-1/4" (83 mm)	4-1/4" (108 mm)
Content of a box	• 20 sq. ft. (1.86 m²)	• 20 sq. ft. (1.86 m²)	• 18 sq. ft. (1.67 m²)
Size of a box	• 85-1/2" L x 9-1/2" W x 3-1/4" H	• 79-1/2" L x 10-1/4" W x 3-1/4" H	• 86" L x 9" W x 3-1/4" H
Weight of a box	• 51 to 59 lb	• 51 to 59 lb	• 46 to 53 lb
Content of a pallet	• 48 boxes = 960 sq. ft. (4 boxes/W x 12 boxes/H)	• 48 boxes = 960 sq. ft. (4 boxes/W x 12 boxes/H)	• 48 boxes = 864 sq. ft. (4 boxes/W x 12 boxes/H)
Size of a pallet	• 85-1/2" L x 38-1/4" W x 42" H	• 79-1/2" L x 42" W x 42" H	• 86" L x 37" W x 42" H
Relative species hardness			
NWFA Janka Test	• Red Oak	1,290 lbs - average hardness	
Hardness test (ASTM-D-143)	• Oak	1,290 lbs - average hardness	
	• White Oak	1,360 lbs - 5% harder	
	• Maple	1,450 lbs - 12% harder	
Red Oak 1,290 lbs* - 100% *lbs = Applied force in pounds			

* Cashmere® is a registered trademark used under license.

1. Values in millimeters have been rounded to the nearest unit. Please refer to values in inches to get the exact planks value.