



Characteristics	Mirage TruBalance Lite	
	Herringbone	
Description	<ul style="list-style-type: none"> <li>Structured prefinished hardwood flooring</li> <li>Micro-V bevel (on 4 sides)</li> <li>Incomparable <b>tongue and groove</b> fit for remarkable uniformity</li> </ul>	
Thickness	9/16" (14 mm) (Real Hardwood Top Lamella 3 mm, Locally Sourced SPF Quarter Sawn* Core layer 9 mm and Wood Backing Veneer 2 mm)	
Width	5" (127 mm)	
Length	Fixed 20" (508 mm)	
Installation	Glued down (above, on or below grade)	
Subfloor	Wood, concrete or radiant heat system	
Species	4 species: White Oak, Red Oak, Oak, Maple	
Grade	<ul style="list-style-type: none"> <li><b>Exclusive:</b> Wood planks with some pronounced and nuanced coloration. The Exclusive grade offers a limited range of color variation.</li> <li><b>Character:</b> These floors are appreciated for their pronounced color variations. They feature open and closed knots, mineral streaks, surface holes, and other character or milling marks. Some distinctive marks may become prominent over time due to changes in the environment.</li> </ul>	
Color choice (Refer to 2026 Mirage Collections)	Some products may not be available. Ask your Mirage representative or consult the <a href="#">Product Chart</a>	
Finish	<ul style="list-style-type: none"> <li>DuraMatt® (5-10% gloss)</li> <li>DurAlive™ (12% gloss)</li> <li>Cashmere*** (18% gloss)</li> <li>Commercial (18% gloss)</li> </ul>	
	UV Protection: All products Static Friction Coefficient (ASTM-D-2047): Slippery resistance superior to 0.5	
Applicable standards	Surface Burning (ASTM-E-84): <ul style="list-style-type: none"> <li>FSI (Flame Spread Index): 180 Class C</li> <li>SD (Smoke Development): 450</li> </ul>	Surface Burning (ULC-S-102-2): <ul style="list-style-type: none"> <li>FSR (Flame Spread Rating): 195</li> <li>SDC (Smoke Development Classification): 115</li> </ul>
	Critical radiant flux (ASTM-E-648-94a): 0.29 watt/cm <sup>2</sup>	R value: R 0.66 to 0.68 (depends on wood species)
	Formaldehyde and VOC emissions (CDPH 1.2, 2017) : Target product group (TruBalance) conform	
Provenance	Made in St-Georges, Qc, Canada.	
Use	Residential, light commercial or commercial	
Accessory	Matchable Square Stair Nosing, Round Reducer, Threshold, "T" Molding, Quarter Round, Wood Flush Mount Vent Acoustitech underlayments are recommended by Mirage. To know more about the minimum criteria needed regarding the recommended waterproof acoustic underlayment, please refer to the <a href="#">Technical Newsletter #20</a> in the <a href="#">Guides and Support section</a> at <a href="http://miragefloors.com">miragefloors.com</a> .	
Warranty	<ul style="list-style-type: none"> <li>Structural <b>lifetime</b> limited warranty (For the glued down and nailed/stapled installation relative humidity must be maintained within a range of 25% and 70%. For the floated installation relative humidity must be maintained between 30% and 60%)</li> </ul>	<ul style="list-style-type: none"> <li><b>35-year</b> finish warranty for residential applications</li> <li><b>3-year</b> finish warranty for light commercial applications</li> <li><b>5-year</b> finish warranty for commercial applications with Commercial finish</li> </ul>
Patterns	<ul style="list-style-type: none"> <li>Herringbone</li> <li>Double Herringbone</li> <li>Basket</li> </ul>	<ul style="list-style-type: none"> <li>Cube</li> <li>English pattern (bricks)</li> <li>Fence</li> </ul>
Packaging	5" (127 mm)	
Content of a box	29.20 sq. ft. (2.71 m <sup>2</sup> )	
Size of a box	71" L x 10-1/2" W x 4" H	
Weight of a box	43 to 45 lb	
Content of a pallet	36 boxes = 1,051.20 sq. ft. (4 boxes/W x 9 boxes/H)	
Size of a pallet	71" L x 42-3/4" W x 40-1/4" H	
Relative species hardness		
NWFA Janka Test	<ul style="list-style-type: none"> <li>Red Oak, Oak 1,290 lbs - average hardness</li> <li>White Oak 1,360 lbs - 5% harder</li> <li>Maple 1,450 lbs - 12% harder</li> </ul>	
Hardness test (ASTM-D-143)		
Red Oak 1,290 lbs* - 100%		
*lbs = Applied force in pounds		

\* Predominantly Quarter Sawn.

\*\* Cashmere is a trademark used under licence.

1. Values in inches have been rounded to the nearest unit. Please refer to values in millimeters to get the exact planks value.